

TITLE

A COMPOSITION FOR MAKING EXTRUDED SHAPES AND A METHOD FOR MAKING SUCH COMPOSITION

5

BACKGROUND OF THE INVENTION

Field of the Invention

The presently disclosed invention relates to compositions and methods for making composite construction materials.

Description of the Prior Art

For many years wood has been the material of choice for certain structural applications such as decks and porches. However, wood has a major disadvantage in that it is subject to attack from mold, mildew, fungus and insects. Protection from these causes is usually afforded by protective coatings or by treatment with chemicals or metals such as arsenic. However, these protective methods have the disadvantage of requiring periodic maintenance or employing the use of human toxins.

In addition, wood is also subject to color changes as a result of exposure to sunlight or natural elements. In some applications, such as outdoor decks, such reactivity manifests in various ways such as color spots under furniture or mats as well as other undesirable respects.

To avoid these difficulties, in some cases metal materials have been used in prior art construction, as an alternative to wood. Metal materials are impervious to fungus and insect hazards, but they are subject to corrosion processes. In addition, the weight and/or cost of metal materials makes them unsuitable for a number of applications.

To overcome these difficulties, various substitutes for wood decking planks and similar structural members have been developed in the prior art. As an example, U.S. Patent 5,660,016 to Erwin discloses decking plank that is composed of an extruded polyvinyl chloride outer shell that is filled with a rigid polyurethane foam core. As another example, U.S. Patent 6,128,880 to Meenan describes a modular decking system wherein various system components are designed for interlocking or cooperative assembly. However, such specialty systems have often required

special features such as attachment systems for securing the planks. Other improvements in composite decking have been directed to ornamental features, such as shown in U.S. Design Patent Des. 418,926.

In some processes for making composite members, a vinyl polymer is used in combination with wood elements. For example, U.S. Patents 2,926,729 and 3,432,885 describe thermoplastic polyvinyl chloride cladding that is combined with wood members to form architectural components. According to other technology, a thermoplastic resin layer can be bonded to a thermoset resin layer. For example, in U. S. Patent 5,074,770 a vacuum formed preform is treated to modify the polymeric structure of the resin surface and improve adhesion with a thermoplastic resin layer. Processes such as described in U.S. Patent 5,098,496 to Breitigam for making articles from heat curable thermosetting polymer compositions are also known in the prior art.

In other cases, vinyl polymeric materials have been comprised of a vinyl polymer in combination with one or more additives. Both rigid and flexible thermoplastic materials have been formed into structural materials by extrusion and injection molding processes. In some cases, these materials have also included fiber, inorganic materials, dye and other additives. Examples of thermoplastic polyvinyl chloride and wood fiber blended to make a composite material are found in U.S. Patents 5,486,553; 5,539,027; 5,406,768; 5,497,594; 5,441,801; and 5,518,677.

In some instances, foamed material has also been used to make structural members. Foamed thermoplastics are typically made by dispersing or expanding a gaseous phase throughout a liquid polymer phase to create a foam comprising a polymer component and an included gas component in a closed or open structure. The gaseous phase is produced by blowing agents. Such blowing agents can be chemical blowing agents or physical blowing agents. For example, U.S. Patent 5,001,005 to Blaupied discloses foamed core laminated panels wherein a foamed core, such as a thermosetting plastic foam, is provided with flat rigid sheets or webbed flexible facer sheets. The facer sheets are formed of various materials such as glass fibers bonded with resin binders. Other facer materials include paper, plastic, aluminum foil, metal, rubber and wood.

In some cases, processes have been applied in particular to the manufacture of structural components from foamed thermoplastic polymer and wood fibers. One example is shown in

U.S. Patent 6,054,207. Other improvements to foam-filled extruded plastic decking plank have been directed to functional features such as the non-slip surface coating of grit material on acrylic paint that is described in U.S. Patent 5,713,165 to Erwin.

However, in the prior art it has not been known to use a foamed polymer material, particularly polyvinyl chloride, in combination with a glass fiber. As further described in connection with the presently preferred embodiment, it has been found that this combination of foamed polymer and glass fiber affords a material with properties that are especially suited for use as a wood substitute in structural applications. Among other advantages, the material has been found to be highly weatherable in that it resists fading or color change due to exposure to sunlight or environmental element. In addition, the material has been found to have a low coefficient of thermal expansion, a high modulus (bending strength), and high resistance to cracking.

SUMMARY OF THE INVENTION

In accordance with the subject invention, a composition for use in extruded structural components includes a thermoplastic polymer material that is homogeneously imbedded with glass fibers. The composition further includes internal closed cells or voids. Preferably, the composition includes glass fibers in the amount of 1% to 18% by weight and thermoplastic polymer material in the amount of 82% to 99% by weight. Also preferably, the thermoplastic material is polyvinyl chloride having closed voids or cells therein, which voids or cells, in the aggregate, include between 30% to 70% of the volume of the material. Also preferably, the composition has a specific gravity in the range of 0.5 to 1.0.

Also in accordance with the presently disclosed invention, a method for making a structural shape includes the steps of combining a thermoplastic polymer material with glass fibers as ingredients to form a homogeneous feed material. The thermoplastic polymer material in the feed material is then liquified and blended with the glass fibers to form a thermoplastic/glass melt wherein the concentration of glass fibers is in the range of 1% to 18% by weight. The thermoplastic/glass melt is exposed to a blowing agent that cooperates with the thermoplastic/glass melt to form closed cells in the melt. The thermoplastic/glass melt is then extruded through a die to produce a length of a structural member with a cross-section that defines a predetermined profile.

Preferably, the method for making the structural shape further includes mixing a blowing agent with the thermoplastic material and the glass fibers to form a homogenous feed material, said blowing agent thereafter chemically reacting in response to increased temperature of the thermoplastic/glass melt to release gases that combine with the melt to form the closed cells therein. Also preferably, the chemically reacting blowing agent is selected from the group consisting of azodicarbonamide, citric acid and sodium bicarbonate.

Alternatively, the method includes mixing a blowing agent with the thermoplastic/glass melt to physically form closed cells in the melt. In this case, the physical blowing agent can be used alone or in combination with a chemical blowing agent. Preferably, the physical blowing agent is selected from the group consisting of nitrogen, carbon dioxide, butane, and chlorofluorocarbon.

More preferably, the composition that is made according to such method includes a thermoplastic material of polyvinyl chloride in an amount of 82% to 99% by weight and glass fibers in an amount of 1% to 18% by weight. Most preferably, the glass fibers have a screen size in the range of 1/64 inch to 1/4 inch; a fiber diameter in the range of 5 microns to 30 microns; and a fiber length in the range of 50 microns to 900 microns.

Other features, advantages, and objects of the presently disclosed invention will become apparent to those skilled in the art as a description of a presently preferred embodiment thereof proceeds.

BRIEF DESCRIPTION OF THE DRAWINGS

Presently preferred embodiments of the disclosed invention are shown and described in connection with the accompanying Figures wherein:

Figure 1 is a schematic diagram that illustrates a preferred embodiment of the process for making the disclosed composition;

Figure 2 is a cross-section of the extruder illustrated in Figure 1 at the location indicated by lines 2-2 in Figure 1;

Figure 3 is a schematic diagram that illustrates another preferred embodiment of the process for making the disclosed composition; and

Figure 4 is a diagram of gas injection apparatus that is used in combination with the extruder that is illustrated in Figure 3.

DESCRIPTION OF A PREFERRED EMBODIMENT OF THE INVENTION

As shown in Figure 1, an extruder 10 includes a power drive and gear box 12 that is mechanically coupled to an extruder barrel 14. Extruder 10 further includes a feeder 16. Preferably, extruder 10 is a conical twin screw extruder of the type such as is available from Milacron, Inc. or equivalent. However, commercially available single screw or parallel twin screws extruders can also be used in the practice of the disclosed invention.

As well known to those skilled in the relevant art, in such commercially available extruders the feed material flows from the feeder 16 to the input end 18 of the barrel 14. According to the preferred embodiment of Figures 1 and 2, barrel 14 defines an internal tapered chamber 20 that is aligned along a longitudinal axis 21 that extends between the input end 18 and the output end 22 of barrel 14. In the preferred embodiment of Figures 1 and 2, extruder 10 is a conical twin screw extruder so that the cross-sectional area of chamber 20 decreases along longitudinal axis 21 at longitudinal positions along axis 21 moving in the direction away from the input end 18 and toward the output end 22. Extruder 10 further includes screws 24 and 25 (Figure 1 only) that are located in the tapered chamber 20 and are mechanically coupled to the gear box 12.

As is also well known to those skilled in the relevant art, when the gear box is powered, it causes extruder screws 24 and 25 to rotate in chamber 20 as feed material is supplied from feeder 16 to the input end 18 of barrel 14. The rotation of extruder screws 24 and 25 carries the feed material through chamber 20 in the direction toward the output end 22 of barrel 14. A die 26 having a die port with a selected perimeter profile is connected to the barrel 14 at output end 22. As the feed material passes from the input end 18 to the output end 22 of barrel 14, the cross-sectional area of the chamber 20 decreases and the feed material is compressed. The compression and frictional forces on the feed material cause the pressure and the temperature of the feed material to increase. At some point in chamber 20 of the barrel 14 between input end 18 and output end 22, the temperature is elevated to the point that feed material forms a fluid melt. At end 22 of barrel 14, the fluid melt is forced through the port of the die 26 to produce an extruded length. The extruded length of material has a cross-sectional profile in the direction normal to the longitudinal axis 21 that corresponds to the profile of the die port in die 26.

In accordance with the presently disclosed invention, the feed material includes, as ingredients, a thermoplastic polymer material and glass fibers. As herein disclosed, the thermoplastic polymer material is selected from the group consisting of polyvinyl chloride, polyethylene, and polypropylene. Preferably, the thermoplastic polymer material is polyvinyl chloride beads because polyvinyl chloride has been found to result in a composition that is highly weatherable. The polyvinyl chloride and glass fibers are combined by mixing them together or by blending them together in feeder 16 as the material flows from feeder 16 to the input end 18 of barrel 14. In either case, the polyvinyl chloride and glass fibers form a feed mixture that is fed into barrel 14 at input end 18.

Inside barrel 14, screws 24 and 25 convey the feed mixture through chamber 20 in the general direction along axis 21 away from input end 18 and toward output end 22. As the feed mixture passes through chamber 20, the polyvinyl chloride/glass fiber mixture is compressed. The increasing temperature of the feed mixture in the extruder barrel 14 causes the polyvinyl chloride to melt or liquify and combine with the glass fibers to form a thermoplastic/glass melt of polyvinyl chloride that is imbedded with glass fibers. The thermoplastic/glass melt or polyvinyl chloride/glass melt is thereafter extruded through the die port of die 26 to form a member having the selected cross-sectional profile.

It has been found that if the glass fibers that are used in the feed mixture have parameters within selected ranges, the extruded product will have a relatively high modulus, i.e. a greater bending strength. Such composition is particularly useful in certain applications such as outdoor decking wherein the extruded product will be exposed to relatively high shear loading. In accordance with the disclosed invention, the glass fibers have the following parameters: screen size 1/64 in. to 1/4 in.; fiber diameter 5 μ to 30 μ ; fiber length 50 μ to 900 μ ; and bulk density of 0.275 grams/cc to 1.05 grams/cc (where μ symbolizes microns).

Figures 1 and 2 illustrate a preferred embodiment of the disclosed invention in which a chemical blowing agent is used as a feed mixture ingredient in combination with the thermoplastic polymer material and the glass fiber. The chemical blowing agent is a foaming agent that is mixed with the thermal plastic material and glass fiber as a component of the feed mixture. The chemical blowing agent can be mixed with the polymer material and glass fibers to form a feed mixture, or it can be blended together with the polymer and glass as those materials are fed from feeder 16 to the extruder feed input.

In the embodiment of Figures 1 and 2, as the extruder screws 24 and 25 convey the feed material from the input end 18 of chamber 20 to the output end 22, the chemical blowing agent reacts chemically in response to the increase in temperature and pressure in the chamber 20 of the extruder barrel 14. The chemical reaction of the blowing agent produces reactant gases that mix with the thermoplastic/glass melt to form closed internal cells in the thermoplastic/glass melt. In the preferred embodiment, the closed cells define voids in the composition which voids compose in the range of 30% to 70% of the volume that is defined within the surface of the finished composite member. The closed cells formed by the chemical blowing agent reduce the density of the thermoplastic/glass melt and, thereafter, also reduce the density of the extruded shape. Preferably, the specific gravity of the composite material is in the range of 0.5 to 1.0.

Chemical blowing agents such as described herein can be of either an exothermic or endothermic type. The exothermic blowing agent creates heat as it decomposes. A preferred example of an exothermic blowing agent in accordance with the invention herein disclosed is azodicarbonamide. When sufficiently heated, azodicarbonamide decomposes to nitrogen, carbon dioxide, carbon monoxide, and ammonia. The endothermic blowing agent absorbs heat as it decomposes. Examples of a preferred endothermic blowing agent in accordance with the presently disclosed invention are sodium bicarbonate and citric acid. Also, the endothermic and exothermic blowing agents can be used in combination. For example, azodicarbonamide can be combined with citric acid and with sodium bicarbonate.

In the presently disclosed embodiment of Figures 3 and 4, the barrel is further provided with injection ports 28 and 30. Injection ports 28 and 30 are used to introduce a physical blowing agent that is intended to reduce the density of the melt as is more specifically described herein. As shown in Figures 3 and 4, the blowing agent is introduced through the extruder barrel and the injector assembly into the melt. In some extruding applications, increased pressure and temperature of the thermoplastic material causes off gases to be produced at the end 22 of extruder barrel 14. Vents are sometimes provided in the extruder barrel for the purpose of establishing a decompression zone for releasing unwanted gasses. However, in the embodiment that is illustrated in Figures 3 and 4, there is no decompression zone.

Similarly to the chemical blowing agent, the physical blowing agent causes the melt to incorporate, internal, closed cell structures in the liquid melt. In accordance with the preferred embodiment of Figures 3 and 4, the blowing agent is of the type that is a physical blowing agent

that is a gas. The physical blowing agent is injected through the injection system that is illustrated in Figure 4 and through the extruder barrel 14 into the thermoplastic/glass melt. In accordance with the preferred embodiment, the physical blowing agent can be a pressurized gas such as nitrogen, carbon dioxide, fractional butanes, or chlorofluorocarbons. The gas delivery pressure must be greater than the melt pressure. Typical injection pressures are in the range of about 2,000 to 4,000 psi. The physical mixing takes place in the area of internal chamber 20 between the injector ports 28 and 30 and the die 26.

The injector assembly shown in Figure 4 includes two nozzles 32 and 34 that are connected to a tee 36 by lines 38 and 40. Tee 36 is connected to a pressurized gas supply 42 through a control valve 44, a regulator 46, and lines 48, 50 and 52. In the operation of the injector assembly, a physical blowing agent of pressured gas is injected at pressure that is relatively higher than the pressure in internal chamber 20 at the location of nozzles 32 and 34. Typically, the injection pressure is in the range of 2000 to 6000 psi. The gas blowing agent flows from the gas supply 42 through regulator 46, control valve 44, tee 36 and lines 38 and 40 to nozzles 32 and 34. The gas blowing agent flows from nozzles 32 and 34 into the chamber 20 of the extruder 10 and mixes therein with the liquid polymer or melt. When mixed with the injected gas, the polymer forms internal closed cells. As with the chemical blowing agent, the physical blowing agent is exposed to the melt and results in closed cell voids that compose in the range of 30% to 70% by volume of the total melt. Specific gravity of the melt is in the range of 0.5 to 1.0. This closed cell structure results in a lower density of the melt as well as a lower density of the extruded material after the melt is extruded through die 26 to produce a lineal product having a profile that corresponds to the shape of the die port in die 26.

Alternatively, chemical blowing agents as herein disclosed in connection with Figures 1 and 2 can be used in combination with physical blowing agents as disclosed in connection with Figures 3 and 4.

The combination of the polyvinyl chloride/glass melt in the presence of a blowing agent has been found to result in a composite extrusion that is weatherable and that is of appropriate density to use as a substitute for lumber in applications such as outdoor decking. Furthermore, it is believed that due to the use of the glass fibers, the disclosed composition has a high modulus and a low coefficient of thermal expansion. The closed cell extruded composition of glass fibers and polyvinyl chloride has been found to have preferred mechanical properties – namely, greater

tensile, flexural, and impact strength. It has also been found to have greater dimensional stability and less mechanical distortion in response to temperature increases.

While several presently preferred embodiments of the invention have been shown and described herein, the presently disclosed invention is not limited thereto but can be otherwise

5 variously embodied within the scope of the following claims.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2